

The Agent

Covert Security & Surveillance

Fully Portable, Battery Operated with Voice Alarm Messages via radio.

The Lookout Agent is a fully portable covert security and surveillance system that transmits voice alarm messages over radio. The content of these voice alarms can be customized by the user to announce detailed alarm information in any language. The range capability of the transmission is determined by the range of the user's current communication system. Radio systems include, but are not limited to, UHF, VHF, 800 Mhz, 900 Mhz and trunking.

Disguised as a briefcase, the Agent is designed for a variety of covert investigation operations. The system comes complete with a four-channel wireless sensor receiver and four wireless sensors (PIR, panic button, door contact and tilt) and is configured for the user's radio system. A microprocessor permits programming of the Agent by computer software (LookPC) and/or with the DTMF tones that are generated through the keypad on any user's radio. The Agent is also equipped with a connector which may be used to trigger an on-site camera or other peripheral device.

Under normal conditions, the Agent operates on its gel-cell battery for an average of 500 hours between battery charges (depends on number of radio broadcasts). When a battery charge is needed, the Agent transmits a verbal "low battery" message. The internal battery is recharged by connecting the system to a small wall charger for about 10 hours. Full charge will be indicated by a green LED.

Applications

Covert Operations

Vehicle Protection

Sting Operations

Internal Theft
Investigations

Rapid Deployment

Backup Detection

Surveillance

Exhibit Security

Emergency Coverage

Executive Protection

**Remotely Programmable
and Completely Wireless**



Manufactured in the USA by
Intellitech Industries, Inc.
4040 Royal Drive Kennesaw, GA 30144
800-207-6269
(770) 514-7999 fax (770) 514-1285
www.lookoutportablesecurity.com

LOOKOUT[®]
PORTABLE SECURITY SYSTEMS

Specifications and Features

- **Clock Calendar** - Permits automatic enable or disable of individual sensor zones based on user programmable schedule. Set schedules by hour of day, day of week or holiday.
- **PC Software** - The Agent has specially designed software (LookPC) that allows extensive user programmability for maximum flexibility in system setup. Features include sensor scheduling, status reports, alarm history, triggering external devices, and more.
- **Custom Message Capability** - In addition to the factory recorded alarm and status messages, precise voice messages may be recorded and assigned to individual sensor zones and Agents. The length of these messages is user-determined up to 15 seconds. This feature permits the use of other languages and message encoding.
- **Self-Test Transmission** - Users may select and schedule periodic status reports from the Agent, ensuring system confidence and reliable management of the remote system.
- **Battery Powered** - The Agent is equipped with a 7.5AH gel-cell battery which will operate unattended for an average of 500 hours. The system is also equipped with an optimum charge cycle battery charger to maximize battery life.
- **Supervised Key Switch** - Power on and power off messages are broadcast over the user's radio system.
- **Entry / Exit Delay** - Allows entry and exit into the protected area without setting off a sensor.
- **Outputs** - A supplied 5 watt broadcast radio (UHF and VHF only) provides voice output directly to security or law enforcement radios. Special radios such as 800 Mhz and trunking are not included. The Agent can be configured for special radio systems. Consult the factory for details regarding your radio system. A single SPDT contact output can be set to activate on alarm or can be activated remotely by DTMF command.
- **Remote Programming Via DTMF Tones** - Programming features can also be done remotely thru any radio with a DTMF keypad. NOTE: Some radio systems have keypad tones disabled. Consult your radio supplier and/or technical service personnel to see if you can use this feature.
- **Internal Memory of Alarms** - The system maintains a memory of the last 100 alarms by time, date and sensor. The memory log can be retrieved thru the LookPC software or by using a remote DTMF command.
- **Housing** - Commercial grade vinyl briefcase 19 x 15 x 4.5. The Agent can be special ordered in an outdoor case.
- **Green LED** - Indicates full battery charge. **Red LED** - Indicates battery charging.
- **Environmental** - Designed for indoor use unless otherwise specified.
- **Temperature** - Operable at -15C to 30C (0F to 120F)
- **Humidity** - 5% to 95% RM (non-condensing)
- **Detection Methods** - Wireless PIRs, panic buttons, door switches, tilt sensors, or your own sensors can be monitored by the Agent. The Agent monitors 4 zones which can have an unlimited number of sensors per zone. In addition, when a PIR sensor has a low battery, the Agent can report a sensor low battery message. A general purpose transmitter is used to interface other types of sensors.

Radio The Agent is factory equipped with a UHF or VHF business band radio system. The transceiver is mounted inside the briefcase. Standard frequencies include VHF (136-174Mhz) and UHF (405-460 Mhz, 440-460 Mhz, 450-470 Mhz). The Agent is also compatible with most commercially available radio systems, including 800Mhz and 900 Mhz systems, with or without trunking

capability. Call for more details about how we can configure the Agent for your radio system.

Telephone The Agent can also be configured with a cellular phone or a standard phone line. Cellular phone is factory installed. Ask your Lookout representative for details.